



Knapsack & Compression Sprayers



X-15

MANUAL KNAPSACK SPRAYER

- AGRICULTURE**
- HORTICULTURE**
- TIMBER TREATMENT**
- PEST CONTROL**
- DISINFECTANTS**
- INDUSTRIAL APPLICATIONS**
- GARAGES**



<p>TANK LID: 115mm diameter that facilitates filling and cleaning operations</p> <p>PUMPING LEVER: Resistant and easily operated. Can be installed for both left and right hand operation</p> <p>VPC-CONSTANT PRESSURE VALVE: Provides even flow rate and spray angle. Reduces the pumping pulsations with better use of the pressure accumulated in the chamber. Improves safety and quality of applications. Pressures 1 or 2 bar</p> 	<p>X-15 HAS BEEN TESTED FOR MORE THAN 2,500 HOURS PROVING TO BE HIGHLY RESISTANT TO WEAR</p> 	<p>PRESSURE MECHANISM: Large capacity chamber that reduces the number of pumping pulsations: Made of plastic, it is highly resistant to chemical action</p> <p>STRAPS: Padded straps for added user comfort with simple adjustable fittings</p> <p>TANK: 15 litres, made of high density polyethylene. It resists impact and corrosion. Contoured for user comfort</p> <p>TRIGGER VALVE: Equipped with constant flow locking device. Trigger removable for use as wrench to service the needle fitted with filter</p>
--	---	---

<p>Flow Calibrator Bottle: the easiest and fastest way to calibrate a knapsack sprayer reducing waste and damage to the environment</p>	<p>Spray Hood: To prevent drift and avoid contact of non selective herbicides with the crop</p>	<p>Spray Lance 160: Mounted with 2 nozzles to improve penetration specially on perennial crops</p>	<p>Pliable Boom 3 Nozzles: Hold the required shape for better coverage of row crops</p>	<p>Boom 500-2 Nozzles: Improves coverage increasing productivity</p>	<p>Extension 700: Increases the application reach on garden beds or high trees</p>
--	--	---	--	---	---

X-15 has optional accessories to meet a variety of herbicides, insecticides and fungicide applications

TECHNICAL SPECIFICATIONS	
<p>Weight (empty tank): 4.8kgs Capacity: 15litres Material: High Density Polyethylene Lid Diameter: 115mm Operational Side: Both, left and right Installed Nozzle: fan, flood, cone and adjustable nozzle Recommended for use with Creosote</p>	<p>Pump Type: piston Material: polyamide Capacity: 80cc Working Pressure: 1-6bar Brass Spray Lance: Length: 600mm Hose: Length: 1350mm</p>