

# CAMON<sup>®</sup>

## LA25

## AERATOR

 **MADE IN  
BRITAIN**

### **SIMPLE OPERATION**

with a straightforward lever that engages the tines.

### **ANTI VIBRATION HANDLEBARS**

with the option of rubber mounts to reduce vibration even further.

### **POWERFUL HONDA ENGINE**

### **QUICK FOLDING HANDLEBARS**

for storage and travel convenience.

### **CHOICE OF TINES**

allowing the user to select the perfect tine for the job.

### **ADJUSTABLE TINE DEPTH**



► SEE WEBSITE

Aeration plays a pivotal role in lawn health, and the **CAMON LA25** is your perfect tool for fostering robust and vibrant grass. With its six interchangeable tine options, you can cater to your lawn's needs all year round, alleviating soil compaction, enhancing drainage, and optimizing nutrient circulation.

## CAPABILITIES

The **CAMON LA25** combines power and compactness, setting the bar high with its versatility in tine selection and short change-over time. Transitioning between hollow corers, chisel tines, or fracture tines is a breeze, taking less than 5 minutes. Its straightforward operation allows for rapid and efficient coverage of expansive areas.

Crafted using specialty steels, the **CAMON LA25's** tines promise extended durability, ensuring the aerator can handle rigorous, prolonged usage. Its high-quality gearbox drive mechanism underscores its reliability, making the **CAMON LA25** a valuable tool for many years.

Beyond its rapid tine switches, users can adjust the ground speed and hole-spacing pattern, underscoring its adaptability. With unparalleled build quality, the **CAMON LA25's** versatility stands second to none in the market.

## SPECIFICATION

ENGINE	HONDA GX160
WORKING WIDTH	40CM
AERATION DEPTH	7½CM
TINES INCLUDED	10MM SOLID TINES HOLLOW CORERS
WEIGHT	103KG
DIMENSIONS	100CM X 65CM X 68CM



## TINES

The **CAMON LA25** aerator has the ability to change between a range of tines ensuring that the operator always has the best tool for the job.



**10MM SOLID SPIKE**  
INCLUDED AS STANDARD



**15MM SOLID SPIKE**



**HOLLOW CORER**  
21MM OUTER/15MM INNER DIA.  
INCLUDED AS STANDARD



**FRACTURE TINE**  
40MM WIDE



**CHISEL TINES**  
20MM WIDE



**CHISEL TINES**  
30MM WIDE



**CHISEL TINES**  
40MM WIDE

